

PEEK GF30

Smiths High Performance



Revision: SHP/english/datasheets/peek-gf30/12.02.2025

Page: 1 of 1

Plastic with 30% glass fibre fill

PEEK GF30 is a high-performance plastic reinforced with glass fibre.

As with all our plastic derivatives, PEEK GF30 offers the same performance characteristics as our standard material, VICTREX™ PEEK™ 450G.

The addition of glass fibre increases the performance characteristics even further.

PEEK GF30 combines high rigidity with superior dimensional stability, providing very high stiffness and improved toughness. This performance plastic has the best static load over extended periods in higher temperature service. Tipped tooling is necessary when machining due to the material's glass fibre content.



Characteristics:

- High rigidity and superior dimensional stability
- Higher compression capability
- Higher continuous service temperature
- Very high stiffness and Improved toughness
- Best high static load over long periods at high temperature
- Less suitable for bearing and wear application

Applications:

- Strut mounts front and rear suspension
- Control arm linkages
- Gear link bushes
- Fuel line insulators
- Valve components
- Electrical components
- Chassis components

About Smiths High Performance

Smiths High Performance is a leading stockholder and supplier of high-performance engineering materials. We are material supply chain partners supporting high-technology market sectors.

www.smithshp.cominfo@smithshp.com

Unit 3, Juno Place
Stratton Business Park
Biggleswade SG18 8XP

Tel: +44 (0)1767 604 708



All information in our data sheet is based on approximate testing and is stated to the best of our knowledge and belief. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of trading.